

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** STIHL Multispray**UFI:** YPM0-20U8-R00J-AK11

[22.07.2019]

**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC24** Lubricants, greases, release products**Application of the substance / the mixture**

Penetrating oil

Lubricant

Anticorrosion additive

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

ANDREAS STIHL AG &amp; Co. KG

Badstr. 115

D-71336 Waiblingen

Tel: +49 (0)7151-26-3237

Fax: +49 (0)7151-26-8-3237

info@stihl.com

**Further information obtainable from:****Headquarter:** see Manufacturer/Supplier**United Kingdom:**

ANDREAS STIHL LIMITED

Stihl House, Stanhope Road,

Camberley, Surrey, GU15 3YT

tel: +44 (0) 1276 20202 / fax: +44 (0) 1276 670502

e-mail: [custservice@stihl.co.uk](mailto:custservice@stihl.co.uk)**Republic of Ireland:**

ORIGO

Magna Drive,

Magna Business Park

Citywest, Dublin 24

tel: +353 (0) 1 4666 726

e-mail: [agreene@origo.ie](mailto:agreene@origo.ie)**1.4 Emergency telephone number:****In England and Wales:** dial 111 (NHS 111)**In Scotland:** dial 111 (NHS 24)**In N Ireland:** Contact your local GP or pharmacist during normal hours;click here ( [www.gpoutofhours.hscni.net](http://www.gpoutofhours.hscni.net) ) for GP services Out-of-Hours.**In Republic of Ireland:** 01 809 2166 (Poisons Information Centre of Ireland)**Germany:** +49 (0) 89 19240 (Poison Centre Munich)**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 1)

**Hazard pictograms**


GHS02

**Signal word** Danger

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

**Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**
**PBT:** Not applicable.

**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**
**Description:** Formulation consisting of pressurised gas and mineral oil with additives in petroleum distillate

**Dangerous components:**

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 1474044-79-5 EC No 939-717-7 Reg.nr.: 01-2119980985-16-xxxx	calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<3%
CAS: 110-25-8 EINECS: 203-749-3 Reg.nr.: 01-2119488991-20-xxxx	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Aquatic Chronic 3, H412	<1%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119555270-46-xxxx	2,6-di-tert-butyl-p-cresol ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410	<0.25%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 2)

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:***Take affected persons out into the fresh air.**Remove soiled clothing***After inhalation:***Supply fresh air.**In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.***After skin contact:***Wash the areas of skin affected with water and a mild detergent.**If symptoms persist consult doctor.***After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *Do not induce vomiting; call for medical help immediately.***4.2 Most important symptoms and effects, both acute and delayed***Breathing difficulty**Headache**Drowsiness**Nausea***4.3 Indication of any immediate medical attention and special treatment needed***Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Foam**Carbon dioxide**Fire-extinguishing powder**Water haze***For safety reasons unsuitable extinguishing agents:** *Water with full jet***5.2 Special hazards arising from the substance or mixture***Can form explosive gas-air mixtures.**In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO<sub>2</sub>)**Phosphorus oxides (e.g. P<sub>2</sub>O<sub>5</sub>)***5.3 Advice for firefighters****Protective equipment:***Do not inhale explosion gases or combustion gases.**Wear fully protective suit.**Do not enter the hazardous area without a self-contained breathing apparatus.**See Section 8 for information on personal protection equipment.***Additional information***Cool endangered receptacles with water spray.**Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Keep away from ignition sources.**Ensure adequate ventilation**Wear protective equipment. Keep unprotected persons away.***6.2 Environmental precautions:***Do not allow to penetrate the ground/soil.**Do not allow to enter sewers/ surface or ground water.***6.3 Methods and material for containment and cleaning up:***Ensure adequate ventilation.*

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 3)

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

When using product on electrical parts disconnect them from power supply first. Before re-assembly, let dry for 2 minutes.

#### Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Store away from foodstuffs.

#### Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

RCP-TWA (EU)	Long-term value: 1200 mg/m <sup>3</sup> , 165 ppm Vapour / Total Hydrocarbons
--------------	----------------------------------------------------------------------------------

#### CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------

#### CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

WEL (Great Britain)	Long-term value: 10 mg/m <sup>3</sup>
---------------------	---------------------------------------

**Regulatory information** WEL (Great Britain): EH40/2020

#### DNELs

#### CAS: 8042-47-5 White mineral oil, petroleum

Oral	DNEL	40 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	92 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		220 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	35 mg/m <sup>3</sup> (consumer) (long-term exposure - systemic effects)

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 4)

	DNEL	160 mg/m <sup>3</sup> (worker) (long-term exposure - systemic effects)
<b>CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)</b>		
Dermal	DNEL	10 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	5 mg/m <sup>3</sup> (worker) (longterm systematic effects)
<b>CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine</b>		
Oral	DNEL	92 mg/kg (consumer) (acute systematic effects)
	DNEL	5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	50 mg/kg (consumer) (acute systematic effects)
	DNEL	10 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	5 mg/kg (consumer) (longterm systematic effects)
	DNEL	100 mg/kg (worker) (acute systematic effects)
	DNEL	9 mg/m <sup>3</sup> (consumer) (acute locale effects)
	DNEL	18 mg/m <sup>3</sup> (worker) (acute locale effects)
	DNEL	0.005 mg/m <sup>3</sup> (consumer) (longterm local effects)
	DNEL	0.01 mg/m <sup>3</sup> (worker) (longterm local effects)
	DNEL	0.1 mg/m <sup>3</sup> (consumer) (longterm systematic effects)
	DNEL	0.2 mg/m <sup>3</sup> (worker) (longterm systematic effects)
<b>CAS: 128-37-0 2,6-di-tert-butyl-p-cresol</b>		
Dermal	DNEL	5 mg/kg (VL)
		8.3 mg/kg (worker)
Inhalative	DNEL	1.74 mg/m <sup>3</sup> (VL)
		5.8 mg/m <sup>3</sup> (worker)

#### PNECs

<b>CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)</b>		
Oral	PNEC	22.2 mg/kg food (human)
	PNEC	10 mg/l (KS)
		0.004 mg/l (water (fresh water))
		0.0004 mg/l (water (sea water))
PNEC		69 mg/kg (sediment (fresh water))
		6.9 mg/kg (sediment (sea water))
		13.9 mg/kg (soil)
<b>CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine</b>		
PNEC		0.0043 mg/l (sporadic release)
		0.00043 mg/l (water (fresh water))
		0.000043 mg/l (water (sea water))
<b>CAS: 128-37-0 2,6-di-tert-butyl-p-cresol</b>		
Oral	PNEC	16.7 mg/kg food (human)
	PNEC	100 mg/l (sewage plant)
		0.004 mg/l (sporadic release)
		0.004 mg/l (freshwater (Süßwasser))
		0.0004 mg/l (sediment (sea water))
PNEC		1.29 mg/kg (sediment (fresh water))
		1.04 mg/kg (soil)

**Additional information:** The lists valid during the making were used as basis.

#### 8.2 Exposure controls

##### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 5)

**Personal protective equipment:**
**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

**Respiratory protection:**

Not required in normal cases

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

**Protection of hands:** Protective gloves

**Material of gloves**

Nitrile rubber, NBR

 Recommended thickness of the material:  $\geq 0.4$  mm

**Penetration time of glove material** Value for the permeation: Level 6 ( $\geq 480$ min)

**Eye protection:** Not required in normal cases

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**
**General Information**
**Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	brown-opaque
<b>Odour:</b>	Solvent-like
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	180 - 270 °C (Active ingredient data )

**Flash point:** 85 °C (DIN 51758)

**Flammability (solid, gas):** Not applicable.

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Not determined.

**Explosive properties:** In use, may form flammable/explosive vapour-air mixture.

**Explosion limits:**

<b>Lower:</b>	0.6 Vol.% (Main ingredient data) 1.5 Vol.% (Propellant data)
<b>Upper:</b>	7.0 Vol.% (Main ingredient data) 10.9 Vol.% (Propellant data)

**Vapour pressure:** Not determined.

**Density at 20 °C:** 0.84 - 0.85 g/cm<sup>3</sup>

**Relative density** Not determined.

**Vapour density** Not determined.

**Evaporation rate** Not determined.

**Solubility in / Miscibility with**

**water:** Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:** Not determined.

**Viscosity:**

**Kinematic at 40 °C:** <20.5 mm<sup>2</sup>/s (DIN 51562)

(Contd. on page 7)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 6)

**9.2 Other information**

No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No dangerous reactions known.

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.

**10.4 Conditions to avoid**

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects** There are no toxicological findings on this mixture.

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**
**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
------	------	-------------------------------

Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
--------	------	----------------------------------

Inhalative	LC50/8h	>5,000 mg/m <sup>3</sup> (rat) (OECD 403)
------------	---------	-------------------------------------------

**CAS: 8042-47-5 White mineral oil, petroleum**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4d	>5,000 mg/l (rat)
------------	---------	-------------------

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

Oral	LD50	>2,500 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>10,000 mg/kg (rabbit)
--------	------	------------------------

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

Oral	LD50	5,000 mg/kg (rat) (OECD 401)
------	------	------------------------------

		>5,000 mg/kg (Ratte) (OECD 420)
--	--	---------------------------------

Inhalative	LC50 / 4h	1.37 mg/m <sup>3</sup> (rat)
------------	-----------	------------------------------

		1.8 mg/m <sup>3</sup> (Ratte) (OECD 403)
--	--	------------------------------------------

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

Oral	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 401)
------	------	----------------------------------------------

Dermal	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
--------	------	----------------------------------------------

**Primary irritant effect:**
**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Repeated dose toxicity**
**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

Oral	NOAEL 90 d	100 mg/kg (rat) (OECD 408, 90d, target organ: liver)
------	------------	------------------------------------------------------

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

Oral	NOAEL	25 mg/kg (Ratte)
------	-------	------------------

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 7)

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

**12.1 Toxicity** There are no ecotoxicological data available on this mixture.

**Aquatic toxicity:**

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

**CAS: 8042-47-5 White mineral oil, petroleum**

LC50 / 96h	>100 mg/l (fish)
EC50 / 48h	>100 mg/l (daphnia)
NOEC/NOEL	≥100 mg/l (fish) (96h)
	≥100 mg/l (algae) (72h)
	≥100 mg/l (daphnia) (48h)

**CAS: 106-97-8 butane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

**CAS: 74-98-6 propane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

**CAS: 75-28-5 isobutane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)**

Inhalative LC50/1	>9 mg/L (rat)
LC50 / 96 h	>0.28 mg/l (fish)
NOEL 21 d	2.2-10 mg/l (daphnia)
EC50	>0.27 mg/l (daphnia)
EC50 / 48h	>0.27 mg/l (daphnia)
IC50 / 48h	>0.27 mg/l (daphnia)
NOEC / 72 h	>0.27 mg/l (algae)

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadeceny)glycine**

LC50 / 96 h	6.8 mg/l (fish)
EC20 / 0.5 h	50 mg/l (activated sludge)
EC50 / 48h	0.43 mg/l (Daphnia magna)
EC50 / 72h	6.3 mg/l (Scenedesmus subspicatus)
	0.91 mg/l (Desmodesmus subspicatus) (OECD 201)

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

LC50 / 96h	>0.57 mg/l (Danio rerio)
EC50 / 48h	>0.17 mg/l (Daphnia magna)
IC50 / 72h	>0.42 mg/l (Desmodesmus subspicatus)
NOEC/NOEL	0.39 mg/l (Daphnia magna)

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 8)

**12.2 Persistence and degradability**
**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Biodegradation 69 % (28d)

**CAS: 8042-47-5 White mineral oil, petroleum**

Biodegradation &gt;60 % (28d (OECD 301B))

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

CSB 2,400 mg/g

Biodegradation 85 % (OECD 301 B Ready Biodegradability - CO2 Evolution)

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

Biodegradation 30 % (MITI-Test II)

4.5 % (---) (OECD Richtlinie zur Untersuchung v. Chem.Nr 301C)

**12.3 Bioaccumulative potential**
**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

BCF 3.16

log POW &gt;6.6 log POW

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

log POW 3.5-4.2 log POW

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

log POW 5.1 log POW

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment** Not applicable.

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10\* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

**14.1 UN-Number**
**ADR, IMDG, IATA** UN1950

**14.2 UN proper shipping name**
**ADR** 1950 AEROSOLS

**IMDG** AEROSOLS

**IATA** AEROSOLS, flammable

**14.3 Transport hazard class(es)**
**ADR**

**Class** 2 5F Gases.

(Contd. on page 10)


**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 9)

<b>Label</b>	2.1
<b>IMDG, IATA</b>	
	
<b>Class</b>	2.1
<b>Label</b>	2.1
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	Void
<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	see Sections 6-8 Warning: Gases.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	D
<b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**European Directives:**  
EC/1907/2006 (REACH)  
EC/1272/2008 (CLP)  
EC/648/2004

**National regulations:**

**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

Aerosols | On basis of test data

**Abbreviations and acronyms:**

vPvB: very persistent and very bioaccumulative  
PBT: persistent, bioaccumulative, toxic

(Contd. on page 11)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version: 6.02

Revision: 26.05.2020

(Contd. of page 10)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**Version history and indication of changes:** Replaces version 6.01.

**\* Data compared to the previous version altered.**